


Compact PROFINET / PROFINET Block I/O Module

Safe Digital Inputs and Outputs, Standard Universal Digital Channels, IO-Link Master Ports


TBPN-L1-FDIO1-2IOL



Type	TBPN-L1-FDIO1-2IOL
ID	6814053
Supply	
Supply voltage	24 VDC
Admissible range	20.4...28.8 VDC
Voltage supply connection	7/8", 5-pin
Electrical isolation	galvanic isolation of the voltage groups V1 and V2, voltages up to 500 VAC
Power dissipation, typical	≤ 5 W
System data	
Fieldbus transmission rate	100 Mbps
Fieldbus connection technology	2 × M12, 4-pin, D-coded
Web server	integrated
Service interface	Ethernet via P1 or P2
PROFINET	
Addressing	DCP
Conformance class	B (RT)
MinCycleTime	1 ms
Diagnostics	acc. to PROFINET alarm handling
Topology detection	supported
Automatic addressing	supported
Media Redundancy Protocol (MRP)	supported
Safety Data	
PL acc. to EN ISO 13849-1	Level e
Category acc. to DIN EN 13849-1:2008	4
SIL acc. to IEC 61508	3
Useful Lifetime	20 years (EN ISO 13849-1)


- PROFINET device
- Integrated Ethernet switch
- 100 Mbps supported
- 2 × M12, 4-pin, D-coded, Ethernet fieldbus connection
- Glass fiber reinforced housing
- Shock and vibration tested
- Fully potted module electronics
- Protection classes IP65, IP67, IP69K
- 5-pin 7/8" male connector for power supply
- ATEX zone 2/22
- CCC-Ex
- Two secure digital SIL3-inputs
- Two secure digital SIL3 channels as FDI or FDO (PP, PM)
- Four secure digital SIL3 FDI channels
- 2 IO-Link Master V1.1 slots

Figure 1



Safety Inputs OSSD	
Low-level signal voltage	EN 61131-2 Type 1 (< 5 V; < 0.5 mA)
High-level signal voltage	EN 61131-2 Type 1 (> 15 V; > 2 mA)
Max. OSSD supply per channel	2 A per C0, C1, C2, C3, 1.5 A at 70 °C please consider derating as shown in Figure 1
Max. tolerance test pulse width	1 ms
Interval between 2 test pulses, minimum	20 ms at 1 ms test pulse width 15 ms at 0.5 ms test pulse width

Figure 2



Safety Inputs floating/antivalent	
Max. loop resistance	< 150 Ω
Max. cable length	max. 1 uF at 150 Ω , limited by cable capacitance
Test pulse, typical	0.6 ms
Test pulse, maximum	0.8 ms
Sensor supply	Versorgung V AUX1/T1 max. 2 A , please consider derating as shown in Figure 1
Interval between 2 test pulses, minimum	900 ms
Additional information	no connection to external potential allowed

Safety Outputs	
Output current in off state	< 5 V
Output current in off state	< 1 mA , suitable for inputs according to EN 61131-2 Type 1
Test pulse, typical	0.5 ms
Test pulse, maximum	1.25 ms
Interval between 2 test pulses, typical	500 ms
Interval between 2 test pulses, minimum	250 ms
Actuator power supply	Versorgung V AUX1/T1 max. 2 A , please consider derating as shown in Figure 1
Max. output current	2 A (resistive) , 1 A (inductive)
Additional information	The load must be mechanically or electrically inert to tolerate the test pulses. When configured as a PPM switching output the negative pole of the load should be wired to the M-terminal of the corresponding output (Pin 2).

Connectivity inputs	
Input delay	M12, 5-pin 2.5 ms
Sensor supply	C4, C5: FSO0 max. 2 A; 500 mA per input C6: V AUX1 max. 2 A C7: FSO1 max. 2 A , please consider derating as shown in Figure 1


Connectivity outputs	
Output current per channel	M12, 5-pin 0.5 A, short-circuit-proof, max. 2 A (resistive)/1 A (inductive) all outputs
Actuator power supply	C4, C5: FSO0 max. 2 A; 500 mA per input C6: V AUX1 max. 2 A C7: FSO1 max. 2 A , please consider derating as shown in Figure 1

IO-Link	
Number of channels	2
IO-Link specification	V 1.1
IO-Link port type	Class A and Class B
Frame type	supports all specified frame types
Supported devices	Max. 32 bytes in/32 bytes out per port
Transmission rate	4.8 kbps (COM 1) / 38.4 kbps (COM 2) / 230 kbps (COM 3)
Power supply	Versorgung V AUX1/T1 max. 2 A , please consider derating as shown in Figure 1

Standard/Directive conformity	
Directive	2006/42/EC Machine Directive 2014/30/EC EMC Directive 2014/35/EC Low Voltage Directive
Vibration test	Acc. to EN 60068-2-6 Acceleration up to 20 g
Shock test	acc. to EN 60068-2-27
Drop and topple	acc. to EN 60068-2-31/IEC 60068-2-32
Electromagnetic compatibility	Acc. to EN 61131-2
Approvals and certificates	CE UKCA ATEX zone 2/22 CCC-Ex FCC statement, UV resistant acc. to DIN EN ISO 4892-2A (2013)
UL Certificate	cULus LISTED 21 W2, Encl.Type 1 IND.CONT.EQ.
Note on ATEX/IECEx	The Quick Start Guide with information on use in Ex areas must be observed.




General Information	
Dimensions (W x L x H)	60.4 x 230.5 x 38.8 mm
Ambient temperature	-40...+70 °C
Storage temperature	-40...+85 °C
Altitude	Max. 5000 m
Protection class	IP65 IP67 IP69K
Housing material	PA6-GF30
Housing color	Black
Connector material	Nickel-plated brass
Window material	Lexan
Material screw	303 stainless steel
Material label	Polycarbonate
Halogen-free	yes
Mounting	2 mounting holes □ 6.3 mm

The data sheet serves as advance information. For definitive values see the corresponding product manual. In this respect, no liability for completeness and accuracy can be applied to the content of this data sheet.





Note
 Ethernet cable (example):
 RSSD-RSSD-441-2M/S2174
 Ident. no. 6914218

M12 x 1 Ethernet





Note
 Actuator and sensor cable/PUR connection cable (example):
 RKC4.5T-2-RSC4.5T/TXY
 Ident. no. 6629805

M12 x 1 Safety Inputs





Note
 Actuator and sensor cable/PUR connection cable (example):
 RKC4.5T-2-RSC4.5T/TXY
 Ident. no. 6629805

M12 x 1 Safety I/O Port




Note
 Actuator and sensor cable/PUR connection cable (example):
 RKC4.5T-2-RSC4.5T/TXL
 Ident. no. 6625612


M12 x 1 I/O Port



Note
 Actuator and sensor cable/PUR connection cable (example):
 Connection of a class A device:
 RKC4T-2-RSC4T/TXL
 Ident. no. 6625604
 Connection of a class B device:
 RKC4.5T-2-RSC4.5T/TXL
 Ident. no. 6625612

M12 x 1 IO-Link





Note

Actuator and sensor cable/PUR connection cable (example):

Connection of a class A device:

RKC4T-2-RSC4T/TXL


Ident. no. 6625604

Connection of a class B device:


RKC4.5T-2-RSC4.5T/TXL

Ident. no. 6625612

M12 x 1 IO-Link



- 1 = FSO1
- 2 = DI/DO
- 3 = GND (V1)
- 4 = C/Q
- 5 = GND (V1)




Note

Power supply cable (example):

RKM52-1-RSM52

Ident. no. 6914149

7/8" Power Supply



- 1 BK = GND V2
- 2 BU = GND V1
- 3 GNYE = FE
- 4 BN = 24 VDC V1
- 5 WH = 24 VDC V2

X1

X2

Module Status LED

LED	Color	Status	Description
ETH1 / ETH2	Green	ON	Ethernet link (100 Mbps)
		flashing	Ethernet communication (100 Mbps)
		OFF	No Ethernet link
BUS	Green	ON	Active connection to a master
		flashing	Ready
	Red	ON	IP-address conflict or Restore Mode or Modbus timeout
flashing		Blink/Wink command active	
ERR	Red/Green	alternating	Autonegotiation or waiting for DHCP/Boot-P addressing
		ON	Diagnostics disabled
		ON	Diagnostics enabled
PWR	Green	On	V, power supply OK
		Off	V, power supply off or below defined threshold of 18 V

LED Status I/O

LED	Color	Status	Description
0...3	Green	On	Channel active
		flashing	Self test
	Red	On	Discrepancy
		flashing	Cross circuit
4...7	Green	On	Channel active
		flashing	Self test (input only)
	Red	On	Discrepancy, overload (output only)
		flashing	Cross circuit
8...11	Green	On	Channel active
		flashing	Overload (output only)
	Red	On	Overload (output only)
		flashing	Overload of supply
12, 14 (IO-Link Port 1 and 2) IO-Link Mode	Green/Red	Alternating	Channel active and overload of supply (input only)
		flashing	IO-Link communication, process data valid
	Red	flashing	IO-Link communication, process data invalid
		On	IO-Link supply OK, no IO-Link Communication
12, 14 (IO-Link Port 1 and 2) SIO Mode	Green	On	Digital Input signal is present
		Off	No input signal
13, 15	Green	On	Digital input or output active
		flashing	Overload of supply
	Red	On	Output active with overload/short circuit
		Off	Input or output inactive

Process Data Mapping of the Single Protocols

For more details on the corresponding protocols see manual.

Accessories

Type code	Ident no.		Dimension drawing
TB-SG-L	100014865	Protective housing for TBEN-L and TBIL-M block I/O modules for use in ATEX Zone 2/22	